



Gas puff fuelling simulation with a combined neutral/HESEL model

Thrysøe, Alexander Simon; Madsen, Jens; Naulin, Volker; Nielsen, Anders Henry; Rasmussen, Jens Juul

Publication date:
2016

Document Version
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

Citation (APA):
Thrysøe, A. S., Madsen, J., Naulin, V., Nielsen, A. H., & Rasmussen, J. J. (2016). *Gas puff fuelling simulation with a combined neutral/HESEL model*. Abstract from 43rd EPS Conference on Plasma Physics, Leuven, Belgium.

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.

Gas puff fuelling simulation with a combined neutral/HESEL model

A.S. Thrysøe¹, J. Madsen¹, V. Naulin¹, A.H. Nielsen¹, J. Juul Rasmussen¹

¹ PPFE, Department of Physics, DTU, DK-2800 Kgs. Lyngby, Denmark

In future magnetic confinement fusion devices, such as ITER, high efficiency fuelling with deep penetration is required for maintaining a sufficient plasma core density. One possible fuelling method is gas puffing, in which neutral molecules are puffed into the scrape-off layer (SOL), where they dissociate, and if the resulting atoms are ionized inside the last closed flux surface (LCFS), they fuel the plasma effectively.

We simulate gas puff fuelling by implementing a module for neutral particles into the HESEL model [1]. The HESEL model is a four-field model based on the Braginskii equations on a 2D drift-plane at the outboard mid-plane, and is capable of describing interchange-driven low frequency turbulence. The domain includes the closed field line edge region as well as the open field line SOL region.

It is investigated to what extend the artificial density source in the HESEL model can be replaced by a more accurate model for the fuelling process by implementing a self consistent dynamical model for the neutral particles. This gives an estimate for the amount of neutrals from gas puffing, which is required to fuel the plasma.

For the fuelling to maintain the amount of plasma particles, the ionization of neutrals inside the LCFS must (on average) balance the integrated flux of plasma across the LCFS, i.e.,

$$\left\langle \int_{\text{edge}} dV n N \langle \sigma_{iz} v \rangle \right\rangle_t = \left\langle \int_{\text{LCFS}} dA \Gamma_n \right\rangle_t, \quad (1)$$

where n is the electron density, N is the neutral atom density, $\langle \sigma_{iz} v \rangle$ is the ionization rate coefficient, Γ_n is the particle flux, and $\langle \cdot \rangle_t$ denotes the temporal average. The volume integral on the LHS is over the volume inside LCFS, and the surface integral on the RHS is over the LCFS.

For typical gas puffing rates it is found that the resulting fuelling only accounts for approximately 15-20% of the required plasma density source. We believe this can be explained by the fact that the domain in the HESEL model is located at the outboard mid-plane, in which area the far highest turbulent flux is concentrated, whereas the gas puffing may reasonably be assumed to be more uniformly distributed across the plasma surface. Thus, accounting for this issue would lead towards a much better balance between the fuelling and the plasma losses through the turbulent flux, which indeed is the dominating loss channel.

References

- [1] J. Madsen et al., (2016), submitted to PoP